

TECHNICAL DATA SHEET

Product Name	RUGAN PULL-UP
Product Description	Durable artificial leather with pull-up surface effect and fleece knitting backing, combining PVC, PU, and textile
Material Composition	- Backing (Fleece Knitting): 18% - PU Layer: 15% - PVC Layer: 67%
Technical Specifications	- Thickness: 1.20 mm - Weight: 500 g/m ² - Abrasion Resistance: 100,000 cycles
Physical Properties	High flexibility, pull-up effect surface, long-lasting performance, suitable for intensive use.
Chemical Properties	Resistant to water, oil, acid, and alkaline substances.
Processing Properties	Easy to sew, cut, and bond with strong adhesives.
Tensile Strength	30 MPa (Mega Pascals) – The maximum tensile stress the material can withstand without breaking.
Tear Strength	27 N (Newton) – The resistance of the material to tearing.
Flame Retardancy	Optional
Applications	Furniture, Interior Design, Contract
Storage Conditions	Should be stored away from moisture, heat, and direct
Recycling and Waste Management	Recyclable, environmentally-friendly waste management

Authorized Signature:

I hereby certify that the information provided in this document is accurate and complete to the best of my knowledge.

Company Name: Salder Deri Tekstil Sanayi ve Ticaret A.Ş.

Authorized Representative: Yasin PALA

Date: 27/07/2024

Signature: _____
SALDER SUNİ DERİ
TEKSTİL SAN. ve TİC. A.Ş.
Hayrabolu / TEKİRDAĞ
Hayrabolu V.D. 7410595318